



Main

Range of product	Xantrex XW
Device short name	XW gateway NA
Product or component type	Communication gateway

Complementary

Product compatibility	Up to 20 single phase GT inverters 8 XW devices
Communication network type	Ethernet Wi-Fi
Feature available	Yahoo widget-based monitoring software Embedded web page for configuration and upgrade Energy and alarm reports via email
Communication of data	System power production Inverter specific power production Lifetime energy production Inverter faults with date and time
Communication port protocol	Xanbus
Port Ethernet	10/100BASE-T
Physical interface	CAN Physical layer 2
Electrical connection	2 connectors RJ45 8 pins for Xanbus 1 connector RJ45 8 pins for Ethernet
Cable length	<= 40 m for Xanbus <= 60 m for Ethernet
Channels utilisation	1-11
Application market	US/Canada
Storage capacity	16 MB
Network security encrypting	WPA WEP
Height	112 mm
Width	190 mm
Depth	45 mm
Product weight	0.207 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Environmental characteristic	R and TTE directive
Standards	2004/108/EC EN 60950-1 IEEE 802.11b IEEE 802.11g IEEE Std 802.3 FCC part 15 class B ICES 003 class B EN 55022 A2 EN 55024 A2 ETSI EN 301489-1 version 1.6.1 ETSI EN 301489-17 version 1.2.1 2006/95/EC